

DEF 尿素系列 DEF System

JIASONG-DEF 加注机 JSDEF-118

JIASONG-DEF dispenser JSDEF-118

- 精度: ±0.5% Accuracy: ±0.5%
- 流量: 0-35L/min Delivery Rate: 0-35L/min
- 进口: ≥0.06mpa Inlet Vacuum: ≥0.06mpa
- 计数范围: 0.00 - 9999.99L Register Range: 0.00 - 9999.99L
- 累计范围: 0.00 - 999999999.99L Totalizer Range: 0.00 - 999999999.99L
- 预置范围: 1.00 - 9999L Presetting Range: 1.00 - 9999L
- 电压: AC380V ± 20% 50Hz ± 1Hz or AC220V ± 20% 50Hz ± 1Hz Power Supply: AC380V ± 20% 50Hz ± 1Hz or AC220V ± 20% 50Hz ± 1Hz
- 防爆电机: 380V, 50Hz, 0.55kw Ex-proof Motor: 380V, 50Hz, 0.55kw
- 环境温度: -40°C to 55°C Ambient Temperature: -40°C to 55°C



JIASONG-DEF 流量计 JSJ4A-DEF

JIASONG-DEF Meter JSJ4A-DEF

- 每转排量: 0.5L Discharge rate of each revolution: 0.5L
- 流量: 5-100L/min Flow range: 5-100L/min
- 工作压力: 0.12Mpa-0.35Mpa Working pressure: 0.12Mpa-0.35Mpa
- 精度: ±0.3% Accuracy: ±0.3%
- 重复性: ≤0.1% Repeat error: ≤0.1%
- 使用寿命: ≥10000000L Working life: ≥10000000L



尿素涡轮流量计K24 Adblue Turbine Meter K24

- 进出口: 1" NPT/BSPT Inlet and Outlet: 1" NPT/BSPT
- 材料: PPS Body Material: PPS
- 流量范围: L5-50GPM(20-200LPM) Flow Range: 5-50GPM(20-200LPM)
- 精度: ±0.5% Accuracy: ±0.5%
- 重复性: ≤0.2% Repeat error: ≤0.2%
- 压力等级: 10Bar Pressure Class: 10Bar



Electronic



Pulse Output

DEF 泵 DEF Pump

- 技术参数 Technical Specification

代号 Model	描述 Descriptions	流量 Flow Rate	电压 AC & DC/Hz	转速 RPM	功率 Power Watt	电流 Amp.max	进出口 Inlet-Outlet
CP11-AC230/50	AC pump 230/50	34L/min 9gpm	230/50	1450	400	1.95	3/4"
CP11-AC120/60	AC pump 120/60	34L/min 9gpm	120/60	1450	400	1.95	3/4"
CP11-DC12	DC pump 12V	36L/min 9.2gpm	12	2800	260	22	3/4"
CP-DC24	DC pump 24V	36L/min 9.2gpm	24	2800	310	13	3/4"



DEF 枪 DEF Nozzle

- 技术参数 Technical Specification

代号 Model	描述 Descriptions	流量 Flow Rate	压力 Pressure/bar	进口 Inlet/BSP
11APP-DEF	Automatic Nozzle	40L/min 10.6gpm	3.4	3/4"
11PPS-DEF	Manual Nozzle	80L/min 21.1gpm	3.4	3/4"



Manual Nozzle



Automatic Nozzle

YB-系列滑片泵


YB-Sliding Vane Pump

- Rotary vane structure, By-pass valve built-in. Pump body HT250. Rotor QT500. For diesel, kerosene, gasoline, food oil and high viscous liquid. Higher efficiency than other pumps with the same power. Obvious advantage in high flow at low revolution.




- 技术参数 Technical Specification

代号 Model	描述 Descriptions	转速 Pump Speed	流量 Flow Rate	最大压力 Max Pressure	真空 Vacuum	尺寸 Ports	电机功率 Motor Power	适用结构 Applicable structure
YB50	50mm/2"	400-640RPM	150-300L/min	5Bar	0.5Bar	2" F BSPP	2.2kW	Coupling Drive/V-belt
YB65	65mm/2.5"	400-640RPM	300-500L/min	5Bar	0.5Bar	2.5" F BSPP	4kW	Coupling Drive/V-belt
YB80	80mm/3"	400-640RPM	600-1000L/min	5Bar	0.5Bar	3" F BSPP	7.5kW	Coupling Drive/V-belt
YB100	100mm/4"	500RPM	1500-1900L/min	5Bar	0.5Bar	4" F BSPP	18.5kW	Coupling Drive/V-belt



减速机结构 Coupling Drive



皮带结构 V-Belt Drive



柴油机驱动 Diesel Engine Drive

YDJ 移动加油车

YDJ Mobile Fuel Unit

- Integrated type with flowmeter, pump, motor, control cabinet, reel. Mainly for fueling ships, large transportation, trucks, trains, military vehicles, aircrafts, etc. High flow rate, accuracy 0.3%, mobile type. Easily use, longer working life.



- 技术参数 Technical Specification

代号 Model	描述 Descriptions	流量 Flow Rate	电机功率 Motor Power	油枪 Nozzle	胶管 Hose
YDJ50	TCS50-C-1Meter/YB50 & YB65Pump	300-400L/min	2.2kW & 4kW 3Phase Ex Proof Motor	1.5"	2"/20m
YDJ80	TCS80-C-1Meter/YB80 Pump	700L/min	7.5kW 3Phase Ex Proof Motor	hose adapter	3"/30m

- Remark
- 1/Single phase motor 220V(non explosion-proof) can be adopted for 2.2KW and 4KW motor.
 - 2/It can adopt preset flow structure.
 - 3/The reel can adopt electric drive. Manual drive is standard supply.
 - 4/Please indicate the special requirements for control cabinet during ordering.

