

电磁阀 Solenoid Valve

● 概论

内置重叠式或并联式电磁先导阀控制,工艺先进,动作可靠;
主阀膜片采用进口特制橡胶,强耐腐蚀,耐低温 -40 ℃;
磁路部件采用特种不锈钢磁性材料,永不生锈或产生剩磁;
当工作压力在 0.3-0.4Mpa 时,关闭主阀,小流量系统为 3 ~ 3.5L/min ,可按用户要求设计。

● Main Features

Controlled by built-in overlapped or parallel-connected electromagnetic precursor valve, with advanced craft and reliable action;
Diaphragm of main valve adopts imported special rubber, with high anti-corrosion and resisting low temperature at -40℃;
Special stainless steel magnetic material never rust or generate remanent magnetism;
Close the main valve when the working pressure is 0.3-0.4MPa, the small flow rate is 3-3.5L/min, which can be designed according to users' requirements.

DSF-20F /25F 隔爆型双流量控制电磁阀 Flameproof double-flow solenoid valve

● 技术参数 Technical Specification

产品型号 Model	DSF-20FA (dSF-20FB)	DSF- 25F
介质 Medium	汽油、燃油、煤油 gasoline, diesel, kerosene	
工作压力 Working Pressure	0.035MPa~0.35MPa	
流量 Flow Rate	3~50L/min	80~90L/min
工作电压 Working Voltage	AC220V AC110V DC24V DC12V	
尺寸 Diameter	20mm 3/4"	25mm 1"



MSF-20F /25F 浇封型双流量控制电磁阀（法兰连接） Flameproof double-flow solenoid valve (flange connection)

● 技术参数 Technical Specification

产品型号 Model	MSF-20F	MSF-25F
介质 Medium	汽油、燃油、煤油 gasoline, diesel, kerosene	
工作压力 Working Pressure	0.035MPa~0.35MPa	
流量 Flow Rate	3~50L/min	80~90L/min
工作电压 Working Voltage	AC220V AC110V DC24V DC12V	
尺寸 Diameter	20mm 3/4"	25mm 1"



MSF-20N/25N 浇封型双流量控制电磁阀（内螺纹） Flameproof double-flow Solenoid Valve (Female Thread)

● 技术参数 Technical Specification

产品型号 Model	MSF-20N	MSF-25N
介质 Medium	汽油、燃油、煤油 gasoline, diesel, kerosene	
工作压力 Working Pressure	0.035MPa~0.35MPa	
流量 Flow Rate	3~50L/min	80~90L/min
工作电压 Working Voltage	AC220V AC110V DC24V DC12V	
尺寸 Diameter	20mm 3/4"	25mm 1"



MSF-20T/25T 浇封型双流量控制电磁阀（外螺纹连接） Flameproof double-flow Solenoid Valve (Male Thread)

● 技术参数 Technical Specification

产品型号 Model	MSF-25T	MSF-25T
介质 Medium	汽油、燃油、煤油 gasoline, diesel, kerosene	
工作压力 Working Pressure	0.035MPa~0.35MPa	
流量 Flow Rate	3~50L/min	80~90L/min
工作电压 Working Voltage	AC220V AC110V DC24V DC12V	
尺寸 Diameter	20mm 3/4"	25mm 1"



D50 大流量电磁阀 High Flow Solenoid Valve

● 技术参数 Technical Specification

介质 Medium	汽油、燃油、煤油 gasoline, diesel, kerosene
工作压力 Working Pressure	0.035MPa~0.35MPa
CV 值	48
工作电压 Working Voltage	AC220V AC110V DC24V DC12V
尺寸 Diameter	G2"

