

>> LPG Series LPG系列



LPG 流量计 LPG Flow Meter

- **特点**
最大工作压力: 18 Bar
每转排量: 0.5L
最小调量: 0.1%
重复性: ≤0.17%
精度: ±0.5%

Characteristic
Max.Working Pressure:18 Bar
Discharge rate per revolution:0.5L
Adjustable Minimum Volume:0.1%
Repeatability:≤0.17%
Accuracy:±0.5%



LPG 分离器 LPG Separator

- **特点**
最大工作压力: 25 Bar
回流压力: 40 Bar
过滤: 0.08mm

Characteristic
Max.Working Pressure:25 Bar
By Pass Pressure:40 Bar
Strainer:0.08mm



LPG 枪 LPG Nozzle

- **特点**
进口: BSPF&NPT 3/4" & 1"
最大工作压力: 25 Bar
LPG Discharge on Disconnect:4.3cc
温度范围: -40℃ - 85℃

Characteristic
Inlet:BSPF&NPT 3/4" & 1"
Max.Working Pressure:25 Bar
LPG Discharge on Disconnect:4.3cc
Temperature Range:-40℃ - 85℃



LPG 电磁阀 LPG Solenoid Valve

- **特点**
直径: 3/4" 20mm
连接: 螺纹
流量范围: 5-50L/min
工作压力: 0-16Bar
电压: AC220V/50Hz
环境温度: -20℃-65℃

Characteristic
Diameter:3/4" 20mm
Connection:Thread
Flow Rate:5-50L/min
Working Pressure:0-16Bar
Voltage:AC220V/50Hz
Ambient Temperature:-20℃-65℃

